

# SPECFLUE

8 Curzon Road, Chilton Ind. Estate, Sudbury, Suffolk CO10 2XW  
T: 0800 90 20 220 F: 01787 880555 email: sales@specflue.com

## PIPE SECTION INSULATION



30mm Pipe section

50mm Pipe section



Insulating rigid 316 stainless steel liners within large existing brick stacks has always been a problem. We can now offer you a tried and tested alternative to back-filling with loose granular insulation. By using the rigid pipe sectional insulation, you can be sure that you have fully insulated the entire flue run. You also know how much to allow within your estimate and will not spend twice as much on loose insulation because the stack is wider than anticipated. Finally, it is still possible to inspect the internal stack after installation, without filling the room with insulation granules.

The pipe sectional insulation is available in 30mm and 50mm thickness to suit diameters of 150 and 200mm id. ( Easily trimmed on site to fit 130 and 180mm id.) Larger sizes available to order. It is supplied in 1 metre sections with a self adhesive overlapped tape seam. Additional 75mm wide foil backed tape can be supplied for the butt jointing of each section and extra security along the flue run.

For thatched property installations we recommend the 50mm thick pipe section due to it's additional insulation values.

The pipe section insulation comes foil backed and is 30mm/50mm thick. They are manufactured from non-combustible rockwool and can withstand continuous operating temperatures of up to 500 deg C. The sections have been tested for water absorption to BS2972 1989 part 12 and are also rot proof, odourless, they do not sustain vermin and will not encourage the growth of fungi, mould or bacteria.