

# SPECFLUE

## PowerFlues

Introducing an electric fan for use on gas fires where a conventional chimney cannot be used.

PowerFlues enable a gas fireplace to be installed anywhere in a room. Depending on the size of fire the fireplace can be up to 10 metres from an outside wall. The PowerFlue extract fan is installed on a suitable outside wall. Standard economical twin wall gas vent connects the fireplace to the PowerFlue, safely extracting outside all the fumes from the fire.



### Requirements:

- The overall fireplace opening dimensions **MUST NOT** exceed 0.4 square metres
- The height of the opening **MUST NOT** exceed 66 cms.
- The minimum angle of canopy from the horizontal **MUST NOT BE** less than 40°.
- The flue outlet **MUST BE** at the top and in the centre of the canopy.
- The input of the fire **MUST NOT** exceed 15kW.
- The gas fire **MUST HAVE** approval for use in a conventional chimney

### Included in the fan:

- All fixing kits including drill bits/bolts/and connections
- Power cable
- Control unit
- Solenoids
- Everything you need – nothing else required except flue!

### Price:

<b>5" Powerflue</b>	<b>@</b>	<b>£255.00 + VAT</b>
<b>6" Powerflue</b>	<b>@</b>	<b>£275.00 + VAT</b>

Note: Only difference is spigot size. 6" always recommended to reduce fan noise.

\*Prices fixed to August 2009.