

## **Declaration of performance**

No: DK 020DoP08052013

- 1. Identification: Schiedel Isokern Kingfire Fireplace
- 2. Type: XL
- 3. Open Fireplace for indoor and outdoor use
- 4. Producer: Schiedel Skorstene A/S, Industrivej 23, DK-7470, Karup

Tlf. 0045 70102011 Fax. 0045 70102088 www.schiedel.dk

Name and contact address: Schiedel Skorstene A/S, Industrivej 23, DK-7470, Karup

Tlf. 0045 70102011 Fax. 0045 70102088 www.schiedel.dk

- 6. Test: Report No. P8-149/2006
- 7. Fraunhofer-Institut für Bauphysik, Notified body with certificate No. 1004 has carried out an initial type

The plant's quality management system ISO 9001:2008 is prior approved and ongoing monitoring, assessment and approvel of the MPA NRW Notified body with Certificate No. MPA NRW Q 224 Report No. 130002382

8. Essential characteristics:

Performance:

Harmonized Standard:

Nominel heat output

17,4 kW

EN 13229:2001 og EN 13229 A2

Flue gas volume flow Minimum chimney draft

10 Pa 44%

Efficiency

NPD

Combustion air Heat resistant

0.354 m<sup>2</sup> Kilowatt

176,8 grams/second

Distance to flammable

material sides and rear wall

75 mm

A1

Fire Class

**Birch and Beech** 

Fuel type Max. firing

9,5 kg. per hour

Cleaning

When needed and NPD

**Hazardous Substances** 

None

Performance of the product, as described in section 1 + 2 is consistent with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer, as listed in section 4.

Signed for and behalf of the manufacturer:

Karup den 08-05-2013

Manager Jøhn Sørensen