

## Declaration of performance

No: DK 021DoP08052013

1. Identification: Schiedel Isokern Kingfire Fireplace
2. Type: XXL
3. Open Fireplace for indoor and outdoor use
4. Producer: Schiedel Skorstene A/S, Industrivej 23, DK-7470, Karup  
Tlf. 0045 70102011  
Fax. 0045 70102088  
www.schiedel.dk
5. Name and contact address: Schiedel Skorstene A/S, Industrivej 23, DK-7470, Karup  
Tlf. 0045 70102011  
Fax. 0045 70102088  
www.schiedel.dk
6. Test: Report No. P8-148/2006
7. Fraunhofer-Institut für Bauphysik, Notified body with certificate No. 1004 has carried out an initial type testing.  
The plant's quality management system ISO 9001:2008 is prior approved and ongoing monitoring, assessment and approval of the MPA NRW Notified body with Certificate No. MPA NRW Q 224 Report No. 130002382
8. Essential characteristics:                      Performance:    Harmonized Standard:  
Nominal heat output                              **18,7 kW**    **EN 13229: 2001+EN 13229 A2**  
Flue gas volume flow                              **115 grams/second**  
Minimum chimney draft                              **10 Pa**  
Efficiency    **45%**  
Combustion air    **NPD**  
Heat resistant    **0,354 m<sup>2</sup> Kilowatt**  
Distance to flammable  
material sides and rear wall                              **75 mm**  
Fire Class    **A1**  
Fuel type    **Birch and Beech**  
Max. firing    **10kg. per hour**  
Cleaning    **When needed and NPD**  
Hazardous Substances                              **None**

Performance of the product, as described in section 1 + 2 is consistent with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer, as listed in section 4.

Signed for and behalf of the manufacturer:

Karup den 08-05-2013

  
Manager John Sørensen