

DÉCLARATION OF PERFORMANCE (DOP)

1. Unique identification code of the product-type :

Flexible pipe, name FLEXLISSE
EN 1856-2 : 2009

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 §4

FLEXLISSE

FLEX LISSE 316 : T600 – N1 – W – V2 – L 50008 – G / T200 – P1 – W – V2 – L 50008 – O
T600 – N1 – W – V2 – L 50010 – G / T200 – P1 – W – V2 – L 50010 – O
FLEX LISSE 316 HD : T600 – N1 – W – V2 – L 50012 – G / T200 – P1 – W – V2 – L 50012 – O
POLYSTAR Plus : T600 – N1 – W – V2 – L 70008 – G / T200 – P1 – W – V2 – L 70008 – O
MULTIFLEX 316 : T600 – N1 – W – V2 – L 70010 – G / T200 – P1 – W – V2 – L 70010 – O
MULTIFLEX 904 T600 – N1 – W – V2 – L 70012 – G / T200 – P1 – W – V2 – L 70012 – O

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer :

Convey the products of combustion from heating appliances to the outside atmosphere.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 §5

EUROTIP
483 Chaussée de Tubize
BE-1420 Braine l'Alleud
Tél. : 0032(0)2.384.80.55
Fax : 0032(0)2.385.18.90
Email : info@eurotip.be

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 §2

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V

System 2+

7. Notified factory production control certification body N°2270-CPR-024/ N°2270-CPR-023 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control

8. Declared performance

Essential Characteristics	Performance	Harmonized technical specification
Compressive strength	In accordance	EN 1856-2 : 2009
Tensile strength	10 meters	
Flexibility	Maximum offset : 30°	
Twist strength	In accordance	
Thermal shock resistance	Designation T600 : Yes Designation T200 : No	
Thermal performance under normal operating conditions	T600 - G T200 - O	
Gas tightness/leakage	N1 P1 (maxi 200Pa)	
Flow resistance of chimney sections, fittings and terminals	According to EN 13384-1	
Normal operating conditions	Flexible pipe negative pressure : T600 → 600°C Flexible pipe positive pressure : T200 → 200°C	
Water and vapour diffusion resistance	YES	
Condensate penetration resistance	YES	
Against corrosion	V2	
Freeze thaw resistance	NPD	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by

Joel VANDOMMELE, EUROTIP / Director

Braine l'Alleud, 09/09/2014