

Declaration of Performance

Tecnoflex Plus – Flexible Twinskin Liner GB-028-DOP-25-06-15



Declaration of Performance

No. GB-028-DOP-25-06-15

1. Unique identification code of the product-type:

Flexible Flue Liner (316L & 904L Liner Options)* EN 1856-2

*includes associated fittings as tested and approved.

Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Manufacturer Identification(s):

Tecnoflex Plus

Designation 1	DN (80 – 400)	T200	P1	W	V2	L50010	O
Designation 2	DN (80 – 400)	T600	N1	W	V2	L50010	G
Designation 3 Designation 4	DN (80 – 400)	T200	P1	W	V2	L70010	O
	DN (80 – 400)	T600	N1	W	V2	L70010	G
Designation 5 Designation 6	DN (80 – 400)	T200	P1	W	V2	L50012	O
	DN (80 – 400)	T600	N1	W	V2	L50012	G
Designation 7 Designation 8	DN (80 – 400)	T200	P1	W	V2	L70012	O
	DN (80 – 400)	T600	N1	W	V2	L70012	G

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Convey the products of combustion from heating appliances to the atmosphere

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Schiedel Chimney Systems Ltd Crowther Estate Washington Tyne & Wear NE38 0AQ UK

Telephone: +44 (0) 191 4161150

Fax: +44 (0) 191 4151263 Email: sales@schiedel.co.uk



5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

7. Notified factory production control certification body No. 0036 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

TÜV Industrie Service GmbH TÜV Süd Gruppe Ridlerstraße 65 D-80339 München

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A





9. Declared performance

Essential characteristics and clauses to EN 1856-2	Performance	Harmonized technical specification
Compressive strength of fittings and	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	- p
supports	NPD	
Tensile Strength	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	
	up to 20m	
Crushing Resistance	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	
	Passed	
Flexibility	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	
	Maximum angle for installation 45° with a maximum bending radius of 3 x Ø	
Torsion Strength	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	
	Passed	
Pulling Force	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	
	Passed	
Resistance to fire	Designation(s) 1, 3, 5 & 7:	
	(DN 80-400): O	
	Designation(s) 2, 4, 6 & 8:	EN 1856-2: 2009
	(DN 80-400): G	211 1000 2: 2000
Gas tightness /leakage	Designation(s) 1, 3, 5 & 7:	
	(DN 80-400): P1	
	Designation(s) 2, 4, 6 & 8:	
	(DN 80-400): N1	
Flow resistance of chimney sections	According EN 13384-1	
Thermal shock resistance	Designation(s) 1, 3, 5 & 7:	
Sootfire Resistance:	(DN80-400): No *as designated O	
Sodille Resistance.	Designation(s) 2, 4, 6 & 8:	
The world is enforced as a sunday according	(DN80-400): Yes.	
Thermal performance under normal operating conditions:	Designation(s) 1, 3, 5 & 7:	
	(80-400): T200	
	Designation(s) 2, 4, 6 & 8:	
	(80-400): T600	





Essential characteristics and clauses to EN 1856-2	Performance	Harmonized technical specification
Durability Water and vapour diffusion resistance	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	
vvaler and vapour diffusion resistance	Yes	
Condensate penetration resistance	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	
	Yes	
Against corrosion	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	
	V2	
Freeze thaw resistance	Designation(s) 1, 2, 3, 4, 5, 6, 7 & 8:	
	Yes	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Michael B	Pall: C	hief Exec	cutive	Officer
-----------	---------	-----------	--------	---------

(name and function)

(signature)

Washington, 25th June 2015

(place and date of issue)